

NUTFIX™ on demand

Your data :


Company : _____ Contact person name : _____
 Address : _____ Postal Code : _____ City : _____
 _____ Country : _____
 _____ Phone : _____ Fax : _____
 e-mail : _____ Web Site : _____
 Industry : _____

1 NUTFIX™ MATERIAL

- STEEL STAINLESS STEEL 316L STAINLESS STEEL HR STAINLESS STEEL ALUMINIUM OTHER

2 BODY

ROUND



- H Standard
 Special : _____ mm
 Ø Standard
 Special : _____ mm


HEXAGONAL



- H Standard
 Special : _____ mm
 Ø Standard
 Special : _____ mm

OTHER

Various specifications :



NOTES : _____

3 BODY END


OPEN END



CLOSED END



OTHER




4 TYPE

FE



PE



PC



RE



FP



NOTES : _____

5 APPLICATION

CHARACTERISTICS OF THE WORKPIECE RECEIVING NUTFIX™

Minimum thickness : _____ mm / Maximum : _____ mm

Material : _____ Hardness : _____

Final product : _____

6 WORKPIECE HOLE DIAMETER

Standard as per La Clusienne

Other diameter : _____ mm

7 THREADS

Ø M _____

Ø UNC _____


Ø UNF _____

standard pitch

fine pitch

other : _____

Threaded length L :



standard

L : _____ mm

WITHOUT THREADS :


no hole

hole Ø : _____ mm

8 MECHANICAL REQUIREMENTS

Standard

Special :



Push-out force : _____ daN

Tensile force : _____ daN

Direct torque force : _____ Nm

Indirect torque force : _____ Nm

Other : _____

9 THREAD LOCK CHARACTERISTICS

Requirements :

First screwing self-locking torque : _____ Nm

First unscrewing self-locking torque : _____ Nm

Fifth unscrewing self-locking torque : _____ Nm

10 FINISH

Corrosion resistance required :

Standard : _____

White rust : _____ h

Red rust : _____ h

Friction coefficient required : _____

Finish required : _____

11 VOLUMES

Batch quantity required : _____

Forecast :

Yearly quantity : _____

2nd year : _____ parts

Application lifetime : _____

3rd year : _____ parts